

GX20 Data Sheet

Last updated: Jul 21, 2021



Datasheet | **GX20**

Meraki Go Security Gateway

GX20



Performance

- Firewall Throughput - 250 Mbp/s
- Recommended for 50 clients or fewer

Interfaces

- WAN Interface: 1x 10/100/1000 BASE-T Ethernet (RJ45)
- LAN interfaces: 4x 10/100/1000 BASE-T Ethernet (RJ45)
- PoE: 1x 802.3af enabled port (15.5W)

Network and Security Services

- Stateful firewall
- Port Forwarding
- DHCP services
- DNS based security powered by Cisco Umbrella (additional subscription required)

Environment

- Operating temperature: 32 °F to 104 °F (0 °C to 40 °C)
- Humidity: 5 to 95% non-condensing
- Kensington lock hard point

Power

- 50W (54V / 0.92 A) Power Supply Included

LED Indicators

- 2 Ethernet status
- 1 power/booting/firmware upgrade status

Physical Dimensions

- 6.83" x 4.41" x 1.04" (173.4mm x 112mm x 26.3mm), not including deskmount feet or mount plate

Warranty

- 1 year hardware warranty

In the Box

- GX20-HW: Meraki Go Security Gateway
- Wall mount and screw kit
- Quick start guide
- PSU and ethernet cable

Model List / Accessories

- GX20-HW-XX Security Gateway - Desktop
- GA-PWR-50WAC 50W Replacement Laptop Style Adapter for GX20

XX = US/UK/EU